

PYLE®



view

**7" Widescreen TFT/LCD Video Monitor
w/Headrest Shroud and Stand**



PLHR76

[HTTP://WWW.PYLEAUDIO.COM](http://www.pyleaudio.com)


Thank you for purchasing the TFT LCD color monitor. To enjoy the features of this device and to ensure years of trouble-free operation, please read this manual carefully and follow the instructions.



Front Panel

- | | |
|---------------------------------|------------------------|
| 1. earphone jack | 2. Audio/Video input |
| 3. Negative adjustment | 4. Positive adjustment |
| 5. Activation of Menu Indicator | 6. Power ON/OFF |
| 7. Light | 8. Remote sensor |

Remote control



1. Power On/Off
2. Brightness -
3. Brightness +
4. Colour -
5. Colour +
6. Contrast -
7. Contrast +
8. Volume -
9. Volume +
10. V1/V2
11. Picture Swivel

Contents and specifications can be subjected to change without prior notice.

[HTTP://WWW.PYLEAUDIO.COM](http://www.pyleaudio.com)

Basic operation

1. Make sure the video and power connection are properly executed.
2. Press MENU to display the adjustments in this order.
Brightness-->Color-->Contrast-->Volume-->Brightness...
3. Adjust the values by pressing AN+ or AN- .
4. The POWER button activates/deactivates the monitor. It is not Necessary to disconnect the power source.

Specification

Screen Size:	7 inch
System:	NTSC/PAL
Power source:	DC12V \pm 10%
Power consumption:	< 9W
Video Input:	Composition Video Signal
Operating Temperature:	0°C \rightarrow 60°C
Storage Temperature:	-20°C \rightarrow 80°C

Headrest bracket



← 1
Suitable for any kinds of car seats. Easy and conveniently installation without damage to the seats. Length can be adjusted (as Picture).



Accessory

- | | |
|---------------------|---------------------|
| 1 x bracket | 1 x headrest shroud |
| 1 x remote control | 1 x user's manual |
| 2 x connection wire | |